



FL6900U

crystal clear
display solutions



FULL HD 1080

Brilliant Power for Crystal Clear Image Reproduction

High Brightness 4000lm

The FL6900U delivers high brightness 4000 lumen images, for presenting in large meeting rooms and conference halls.

Ultra Quiet 29dBA Operation

Fan noise from a projector can get annoying during a presentation or videoconference. But now that's a thing of the past. The FL6900U offers a significantly low noise level of only 29dBA (Low lamp mode). As a result, your audience can enjoy the presentation or conference without noisy distractions from the projector.

Long 4000hrs Lamp Life

Designed with a lamp temperature controlling system, the FL6900U can support a lamp life of up to 4000 hours^(*). The long life lamp provides reductions in overall cost of ownership by decreasing the frequency of lamp replacements.

(*): When used in Low lamp mode. Maximum lamp life at standard mode use is 2,000 hours.

Enhanced Connectivity with RJ-45

A RJ-45 connector provides an audio-visual manager with the ease of a LAN control. Using the included software, you can manage the projectors on your network. An automatic alert can be sent via email to notify you if a projector needs attention.

sRGB

Developed to ensure standard, uniform colour reproduction regardless of the type of display used, sRGB colour profile technology uses independent colour coordinates common in all display technologies. As a result, it helps to eliminate hue variations that occur between different display systems matching the way colours look in real life.

Projector View (Diagnostic System)

To monitor projectors and facilitate maintenance, an incorporated diagnostic system provides control over key projector functions such as power on/off as well as warnings for operating temperature and filter clogging. Controlled via a master PC, this system is ideal for a Local Area Network (LAN) for both academic and business environments.

4000 ANSI LUMENS
4000 HOUR LAMP LIFE
1000:1 CONTRAST RATIO


FL6900U



New FL6900U FULL HD 1080

Input and Output Terminals

- 1 REMOTE IN and OUT terminals
- 2 LAN terminal
- 3 SERIAL terminal (D-Sub 9pin)
- 4 USB (COMPUTER) terminal
- 5 COMPUTER / COMPONENT VIDEO DVI-D (HDCP) terminal (DVI-D 24pin)
- 6 COMPUTER / COMPONENT VIDEO IN 1 terminals (R/P, G/Y, B/P, H/MV, V) (BNC)
- 7 Main power switch: O: OFF 1: ON
- 8 Power jack
- 9 AUDIO IN 1 terminal (Mini jack)
— The AUDIO IN 1 terminal is used for both COMPUTER 1 and DVI input.
- 10 AUDIO IN 2 terminal (Mini jack)
- 11 COMPUTER / COMPONENT VIDEO IN 2 terminal (Mini D-Sub 15pin)
- 12 MONITOR OUT terminal (Mini D-Sub 15pin)
- 13 AUDIO OUT terminal (Mini jack)
- 14 VIDEO IN and audio input terminals
- 15 S-VIDEO IN and audio input terminals




Optional Lenses Line-UP



* For those who already have OL-X500FR, a front cabinet CA-XL6900(FR) is necessary for use.

Dimensions (unit: mm)



Specifications

Model	FL6900U
Display technology	1.1" 3-LCD
Resolution	1920 x 1080 (Total 2,073,600 pixels)
Brightness	4000 lm
Contrast ratio	1000:1 (on/off)
Projection lens	f=51-64mm, F1.8-2.1
Throw ratio	2.01 - 2.56
Offset axis	10:0 (default) with variable H + V powered lens shift (excluding OL-X500FR)
Zoom / Focus	Motorized Zoom & Focus
Picture size	60" - 250" (100"=4.5 - 5.7m)
Source lamp	220W (Shut Off Time 4000Hrs) with Low mode, 275W (Shut Off Time 2000Hrs) with Standard mode
Computer compatibility	Resolution : 640 x 400 (Expand) - 1920 x 1080 (Real) - 1600 x 1200 (Compress) Sync on Green available
Video compatibility	NTSC / NTSC 4.43 / PAL (including PAL-M, N) / SECAM / PAL-60, Component Video ; 480i/p (525i/p), 576i/p (625i/p), 720p (750p 50/60Hz), 1080i (1125i 50/60Hz), 1080p (1125p 50/60Hz), (1080i (1250i 50Hz) is not available) SCART (RGB + 1V sync, only Mini D-Sub 15pin Terminal)
Input terminals	PC ; 5 BNC x 1, Mini D-Sub 15pin x 1, DVI-D(with HDCP) x 1, PC Audio ; Stereo mini jack (φ3.5mm) x 2 Video ; RCA x 1 or BNC x 1, S-VIDEO (4pin) x 1 or S-VIDEO Y/C (BNC), Video Audio ; RCA (L/R) x 2
Output terminals	RGB ; Min D-Sub 15 pin x 1, Audio ; Stereo mini jack (φ3.5mm) x 1 (Variable Out)
Communication terminals	LAN (RJ-45) ; x 1 (Projector control), RS-232C ; D-Sub 9pin x 1 (Direct command is available), USB ; x 1 (for Mouse Cursor Control), Wired remote (IR) ; x 1 (φ3.5mm Stereo mini jack), Wired remote (OUT) ; x 1 (φ3.5mm Stereo mini jack)
Audio speaker	10 W Mono
Dimensions (W x H x D)	443 x 207 x 434 mm / 17.4 x 8.1 x 17.1 inch (Including Detachable Terminal Cover)
Weight	9.8kg / 21.6lbs (Excluding Detachable Terminal Cover)
Power supply	AC100 - 240V, 50/60Hz

* SXGA, XGA and SVGA are registered trademarks of IBM Corporation.

* All brand names and product names are trademarks, registered trademarks or trade names of their respective holders.


Projection Distance with Optional Lenses

Screen Size (inch)	OL-X500SZ		OL-X500LZ		OL-X500TZ		OL-X500FR							
	Shortest (Wide)	Longest (Tall)	Shortest (Wide)	Longest (Tall)	Shortest (Wide)	Longest (Tall)	inch	mm						
60	74	1.9	90	2.3	-	-	-	-	43	1.1				
80	100	2.5	121	3.1	173	4.4	244	6.2	256	6.5	386	9.8	59	1.5
100	125	3.2	152	3.9	220	5.6	307	7.8	319	8.1	464	12.3	75	1.9
150	189	4.8	229	5.8	331	8.4	465	11.8	484	12.3	728	18.5	114	2.9
200	253	6.4	305	7.8	445	11.3	622	15.8	646	16.4	972	24.7	-	-
250	317	8.1	-	-	555	14.1	780	19.8	811	20.6	1217	30.9	-	-


Screen Size and Projection Distance

Refer to the following table to determine the screen size and projection distance.

Front projection



Front projection, ceiling mounting



Diagonal size	Screen size		Projection distance (L)				Lens movable range								
	Height (H)	Width (W)	Shortest (Wide)	Longest (Tall)	H1	H2	W1	W2	W3	W4					
inch	cm	inch	cm	inch	cm	inch	cm	inch	cm	inch	cm	inch	cm		
60	152	29	75	52	133	104	2.6	133	3.4	15	38	4	10	3	7
80	203	39	100	70	177	140	3.5	178	4.5	20	51	5	13	4	9
100	254	49	125	87	221	175	4.5	223	5.7	25	63	7	17	4	11
150	381	74	187	131	332	264	6.7	306	6.5	37	94	10	25	7	17
200	508	98	249	174	443	354	9.0	449	11.4	49	125	13	34	9	22
250	635	123	311	218	553	443	11.2	-	-	62	156	17	42	11	28

* The above figures are approximate and may be slightly different from the actual measurements.



New publication, effective December 2008 Specifications subject to change without notice.